



HAKKA MX

RIMS & WHEELSETS	733	Crest MK4	D30	S28 27.5
Wheel Size (in)	27.5	700	700	27.5
Outer Width (mm)	33	28.4	26	35
Inner Width (mm)	29	25	19	28.6
Rim Weight (g)	455	399	400	380
Rim Material	6066 Aluminum	6069 Aluminum	Carbon	
Drilling	32 Hole		24 Hole	32 Hole
Type	Tubeless			
Wheelset Weight (g)	1720	1703	1504	1570
Section Height (mm)	19.5	18	30	18.35
Spoke Offset (mm)	2.5	1.5	0	4
Spokes	3		2	3
Cross	3			
Spoke Length (mm)**	273	295	Front: 280 D, 278 ND Rear: 278 D, 280 ND*	276
Nipples	14mm Sapim Double Square with Sapim HM Nipple Washers			
ERD (mm)*	563	601	583	564
Axle Standards (mm)	Front: 15x100 / Rear: 12x142			
Max. Rim Pressure (PSI)	40	55	70	40
HUBS	733	Crest MK4	D30	S28 27.5
Brand	Ibis			
Freehub Mechanism	36T 4-Pawl			
Freehub Engagement	10°			
Driver	Sram XD, Shimano 12-Speed Microspline and 11-Speed Hyperglide			
Number of Bearings	x4			
Brand of Bearings	Enduro			
Disc Rotor Mount Type	6-Bolt			
PRICING / MISC.	733	Crest MK4	D30	S28 27.5
Rim	\$100	OEM Only		\$525
Wheelset	\$525	OEM Only		\$1,299
Rim Warranty	7 Years	2 Years		
Hub Warranty	2 Years			
Wheel Build	USA			
Notes	*All measured using Wheelsmith "Rim Rod" ERD sticks, p/n TL002, with 0.25mm Sapim HM Nipple Washers. **D = Drive Side, ND = Non-Drive side. We generally aim for 120kg of spoke tension on both sides of the wheel.			

SPECIFICATIONS SUBJECT TO CHANGE